

# Quality Assurance

100% copper rotor 100% pure electrolite triple coated wire winding

LTB - 4 & 5 grade bearing & bush

High stage carbon signment thrust bearing

**Fabricated ss impeller** 

SS - 410 grade stainless steel shaft with

**INE grinding & balancing** 

SS 304 grade motor body

**CRNO stamping** 

**Fully computerised tested pumps** 



Manufactured by

LODI STEEL (I) PVT. LTD

T.T.C. Industrial area, New Mumbai - 01, INDIA www.sunduspump.com

Authorised Distributor For Karnataka **SUNDUS Motor & Pumps** 

### SS. PUMPS AGENCY

Office: #4/2, TP Lane, SJP Road Cross, Banglore - 2 9008273973 / 9019979106 sspumpkar@gmail.com



### MANUFACTURERS & EXPORTERS







Noiseless operation



**Special thrust** bearing design



Stainless steel jacket













Pure Water For Life



Sandus pump's is one the top-notch manufacturer's of stainless steel submersible pumps & motors. Our focus is to identify & provide a wide range of products for the water supply & liquid transfer applications with high duty points from 1 to 120 m<sub>3</sub>/h manufactured distinctively for individuals with varied technical skills.

### MANUFACTURING

sandus pumps has remarkably developed as a key player to serve its clients in various countries as a multi-national supplier since 1995. We have not only created a niche demand around the world for our cutting edge products but also achieved the global requirements in terms of design and manufacturing for our stainless steel submersible pumps and motors. These high end products are created by seeking global solutions to fortify economics of scale in production which eventually has resulted into higher quality, low life cost and superior cost effectiveness. The fundamental notion behind the manufacturing facility is that, it is equipped with extensive capital equipments and machinery needed to minimize manufacturing costs as well as maintaining quality of the higher standards. Sandus exhibits heavy investment in the state-of-art manufacturing.



#### **CUSTOMER SATISFACTION**

In today's situation, the customer has multiple alternatives to choose: out of which sundus pumps has been a habitual and favoured company with an outstanding evidence for customer satisfaction. we believe in the phrase 'customer is the King" and hence our core proposition is to provide the customers with products and services of top-grade quality at an economical price.

### LOW INSTALLATION COST

stainless steel implies light weight and self balanced hydraulic parts which safeguards higher efficiency with a comparatively small motor and corrosion resistant which means it provides prolonged running of the pump in spite of non-stop usage. We also provide cost-effective prices by matching the cost of a modern stainless steel pumps to the price of major over-haul expenses of a traditional cast iron or plastic pump.

### **Our Products**

V-4 ||

V-6 ||

V-8 ||

Open Well ||

6x4 Pump | |

Self Priming | |

Monoblock Pumps | |



Motors



**Pumps** 



### **Applications**

- **Apartments and Villas** ◀
  - Sprinkler irrigation **≺**
- industrial water supply ◀
- **Drinking water supply** ◀



**Spares** 

# V-4 Single phase pump price list

### V-4 S.P 50Hz 220V LS3A 32mm (1.25")

НР	STAGE	HEAD	RATE
0.75	9	180	
1	12	240	
1.5	15	300	
1.5	18	360	
2	22	440	
2	25	500	
3	29	580	
3	33	600	

### V-4 S.P 50Hz 220V LS5A 40mm (1.5")

НР	STAGE	HEAD	RATE
0.75	6	120	
1	8	160	
1.5	12	240	
2	17	340	
3	21	420	
3	25	500	

#### V-4 S.P 50Hz 220V LS8A 50mm (2")

НР	STAGE	HEAD	RATE
1	15	100	
1.5	7	140	
2	10	200	
3	12	240	
3	15	300	

Payment : cash / D.D. / Cheque

Warranty: 1 year warranty for all warranty claims original invoince is compulsory goods once sold cannot be taken back or exchanges all disputes are subjected to bangalore jurisdiction

## V-4 3 phase pump price list

### V-4 T.P 50Hz 440V LS3A 32mm (1.25")

HP	STAGE	HEAD	RATE
3	29	580	
3	33	660	
4	39	780	
4	45	900	
5	52	1040	
5	60	1200	

### V-4 T.P 50Hz 440V LS5A 40mm (1.5")

НР	STAGE	HEAD	RATE
3	21	420	
3	25	500	
4	33	660	
5	38	760	
5	44	880	
7.5	52	1040	
7.5	60	1200	

### V-4 T.P 50Hz 440V LS8A 32mm (2")

HP	STAGE	HEAD	RATE
3	12	240	
3	15	300	
4	18	360	
5	21	420	
5	25	500	
7.5	30	600	
7.5	37	740	